



OWANDY-CR²

INTRAORAL IMAGING PLATE SCANNER SO COMPACT, YET SO EFFECTIVE...

Owandy-CR² Product Launch document – EN

PDF Compressor Free Version

INDEX

| 1. PRODUCT IDENTITY | 3 |
|----------------------------------|---|
| 2. TECHNICAL SPECIFICATIONS | 5 |
| 3. OUTLINE DRAWING | 6 |
| 4. HOW TO INTRODUCE A PLATE? | 7 |
| 5. KIT / ACCESSORIES DESCRIPTION | 8 |



1. PRODUCTHOENTITY Version



| Key points | Unit design |
|-----------------------------------------------------------------------------------------------------------------------|-------------|
| Stylish, elegant and compact Optimised sensitivity 100% automatic Suitable for all types of scans Ethernet or USB | ©WQUDA-Chi |

Owandy-CR² Product Launch document – EN

| Main competitors rady antages Free Version | | |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 1. Stylish, elegant and compact | The Owandy-CR ² is the smallest system on the market! It design will add a contemporary and hi-tech touch to your treatment room! | |
| 2. Optimised sensitivity | The Owandy-CR ² insure you to produce accurate images at low doses without the risk of overexposure | |
| 3. 100% automatic | Ø button: the Owandy-CR ² is fully automatic! Imaging plate detection, their size and their insertion direction, reading and erasing are automatic: no complicated user interface. Automatic wake up and standby mode. | |
| 4. Suitable for all types of scans | 4 plate sizes to meet your requirements. The Owandy-CR ² can be used for endodontics, prosthetic dentistry, implant surgery and periodontics, as well as in caries diagnosis. | |
| 5. Ethernet or USB | Ethernet or USB, the Owandy-CR ² is easy to use install and to use. the Owandy-CR ² has been developed for a single or multi-user use. Sharing data becomes easier. | |



Owandy-CR² Product Launch document – EN

2. IPECHINIGATES RECIFICATIONS

| Owandy-CR ² scanner model | |
|--------------------------------------|-----------------------------------------------|
| Certification and class | MDD 93/42 –Ann. IX Rule16: Classification IIa |
| Pixel Size | 30μm |
| A/D Conversion | 16 bit input |
| Power supply | 24V +/-10% |
| Current absorbed | 1A |
| Power absorbed | 60W |
| Dimensions and weight of the unit | |
| Weight: | 4,25kg |
| Height: | 104mm |
| Depth: | 286mm |
| Width: | 151mm |


| Intra-oral phosphor plates | |
|-----------------------------------|------------------------------------------------|
| Certification and class | MDD 93/42 – Ann. IX Rule16: Classification IIa |
| External dimensions of each plate | |
| • Size 0: | 22x31mm |
| • Size 1: | 24x40mm |
| • Size 2: | 31x41mm |
| • Size 3: | 27x54mm |
| Phosphor composition | BaSrFBr:Eu |
| Luminescence | 400nm |
| Readout | Within 1h after exposure |








3. **COTCINE DRAW ING:** Version








PIONCTONNERODUEEVAPIDATE?



Hold the protective cardboard cover and plate as shown above.

Use only the new plates provided with the Owandy CR²!



When the **Owandy CR²** is switched on, the green LED will light up. Now insert the protective cardboard cover and plate horizontally into the slot until the green LED starts flashing.



Once the green LED is flashing, remove the The plate is automatically inserted into the protective cardboard cover to leave only the plate.



Owandy CR² on its own.

The LED will be blue when the plate is being scanned.



The scanning process is finished as soon as the You can then remove the plate using the LED becomes white. When the white LED starts protective cardboard cover. to flash, the plate ejects itself automatically.





Owandy-CR² Product Launch document - EN

KDF/CAGGESSORIES DESCRIPTION

Owandy-CR² kit:

| Part number | Description |
|-------------|--------------------------------------|
| 9458900031 | Owandy-CR ² Ethernet 220V |
| 9458900021 | Owandy-CR ² USB 220V |

Kit includes:

- 1 Owandy-CR²
- 2 plates size 0 + 10 paper protections and 50 hygienic single-use protection sleeves size 0
- 2 plates size 2 + 10 paper protections and 50 hygienic single-use protection sleeves size 2
- USB 2.0 cable or RJ45 cable
- Power supply cable
- An installation CD-ROM (drivers, diagnostic tools, QuickVision software)
- User / Installation manual
- CE Declaration of Conformity


Owandy-CR² accessories (NS > 17000000):


| Part number | Description | | |
|-------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|--|--|
| Intra-oral plates (kit contents 4 plates + 20 paper protections) | | | |
| 6158001401 | Size 0 | | |
| 6158001501 | Size 1 | | |
| 6158001601 | Size 2 | | |
| 6158001701 | Size 3 | | |
| 6158002501 | Starting kit (2 plates size 0 + 2 plates size 2 + 10 paper protections + 50 hygienic single-use protection sleeves) | | |
| Box of 100 paper protections for intra-oral plates | | | |
| 4695481501 | Size 0 | | |
| 4695481601 | Size 1 | | |
| 4695481701 | Size 2 | | |
| 4695481801 | Size 3 | | |
| Box of 300 hygienic single-use protection sleeves for intra-oral plates | | | |
| 6158001800 | Size 0 | | |
| 6158001900 | Size 1 | | |
| 6158002000 | Size 2 | | |
| 6158002100 | Size 3 | | |

PDF Compressor Free Version

TECHNICAL FEATURES

| Technology | Re-usable imaging plate PSP: Photostimulable Phosphor plate | |
|-----------------------|----------------------------------------------------------------|--|
| Resolution | 34 pixel/mm - 16 Bits | |
| Pixel size | 30 µm | |
| Scan time | 4 - 9 s | |
| Connection | USB 2.0 & USB 3.0 | |
| | Ethernet 10/100/1000 Mbps | |
| Dimensions | 286 x 151 x 104 mm | |
| Weight | 4.25 kg | |
| External power supply | 100-240 V, 50/60Hz, 60W | |
| Plate size selection | Automatic detection | |
| System standby mode | Automatic function | |
| Plate sizes | Size 0:31 x 22mm, 1024 x 726 pixels | |
| | Size 1:40 x 24mm, 1321 x 792 pixels | |
| | Size 2: 41 x 31mm, 1354 x 1024 pixels | |
| | Size 3:54 x 27mm, 1783 x 891 pixels | |
| Operating system | Windows 7, 8, 10 (32-64 Bits) | |





Medical device class IIa/CE0051. Read carefully the instructions before use.









Owandy Radiology

2, rue des Vieilles Vignes 77183 Croissy-Beaubourg FRANCE Tel.: +33 (0)164111818 info@owandy.com www.owandy.com



DIGITAL SENSORS IMAGING PLATE SCANNER 2D-3D PANORAMICS INTRAORAL RADIOLOGY CAMERAS SOFTWARE