



# Implantology





# Ki-20 Advance


## Features

- Optic LED Control
- Compact Micro motor 40,000 rpm (1:1)
- 9 memory programs can be stored on single motor
- Record medical records on USB
- Displaying the torque graph in real time
- Large LCD display
- Torque Calibration
- Dual irrigation pumps (optional)
- Dual motor (optional)



## Torque calibration

Calibrates the micromotor & the handpiece to the rotational resistance of each individual handpiece. During the operation, high torque accuracy offered.



## Data management

Treatment data can be easily accessed and downloaded using a USB stick. Files can be transferred and added to patient records. \*USB memory stick not included



## Advanced irrigation pump

The pump allows easy set-up of irrigation tubes and is extremely quiet during operation.



▲ Open



▼ Close

## Foot control

- ① Coolant button(4 steps)    ③ F/R change button
- ② Program change button    ④ Foot pedal(speed control)



## Complete sets



MODEL **Ki-20 Advance (Single)**

### Specifications control box only

- Power supply : AC100-120 or AC220-240V 50/60 Hz
- Speed : 10-2,000 (20:1), 7-1,200 (32:1)
- Torque : 80Ncm (20:1), 90Ncm (32:1)
- Weight : 3.5 kg
- Dimensions : W292 x D230 x H104(mm)
- Contents : Control unit, E-type motor, Handpiece, Foot control, Handpiece stand



MODEL **Ki-20 Advance (Dual)**

### Specifications control box only

- Power supply : AC100-120 or AC220-240V 50/60 Hz
- Speed : 10-2,000 (20:1), 7-1,200 (32:1)
- Torque : 80Ncm (20:1), 90Ncm (32:1)
- Weight : 3.9 kg
- Dimensions : W324 x D230 x H104(mm)
- Contents : Control unit, E-type motor, Handpiece, Foot control, Handpiece stand

# Ki-20

## Features

- Optic LED Control
- Compact Micro motor 40,000 rpm (1:1)
- 9 memory programs can be stored on single motor
- Light & compact optic motor for speedy and accurate surgery.




## E-type Motor

### Optic



### Non-optic



## Advanced irrigation pump

The pump allows easy set-up of irrigation tubes and is extremely quiet during operation



▲ Open

▼ Close



## Foot control

- ① Coolant button(4 steps)    ③ F/R change button
- ② Program change button    ④ Foot pedal(speed control)



## Complete sets



MODEL **Ki-20(Optic)**

### Specifications control box only

- Power supply : AC100-120 or AC220-240V 50/60 Hz
- Speed : 20-2,000 (20:1), 13-1,200 (32:1)
- Torque : 70Ncm (20:1), 90Ncm (32:1)
- Weight : 2.6 kg
- Dimensions : W240 x D225 x H108(mm)
- Contents : Control unit, E-type motor, Contra angle Foot control, Handpiece stand



MODEL **Ki-20(Non-optic)**

### Specifications control box only

- Power supply : AC100-120 or AC220-240V 50/60 Hz
- Speed : 20-2,000 (20:1), 13-1,200 (32:1)
- Torque : 70Ncm (20:1), 90Ncm (32:1)
- Weight : 2.6 kg
- Dimensions : W240 x D225 x H108(mm)
- Contents : Control unit, E-type motor, Contra angle Foot control, Handpiece stand